

S.O GEAR OIL XP-HD

HIGH PERFORMANCE AUTOMOTIVE GEAR OIL

DESCRIPTION

S.O GEAR OIL XP-HD is premium extreme pressure automotive gear oil fortified with sulphur-phosphorus and ashless dispersant additives to enhance anti-wear under heavy loading, anti corrosion, anti oxidant, demulsification and anti-foam properties. This oil meets the performance requirements of API service GL-5, MT-1 and MIL-PRF-2105E, and is particularly recommended for hypoid gears, steering boxes and differential gears operating under critically severe conditions.

CHARACTERISTICS

- Outstanding protection against wear and shock
- Excellent thermal stability
- Excellent rust and corrosion inhibition
- Exceptional load-carrying capability
- Extends gear equipment life

APPLICATION

S.O GEAR OIL XP-HD is recommended for hypoid gears, steering boxes, and differential gears operating under critically severe conditions.

TYPICAL SPECIFICATION

SAE GRADE		140
Kinematic Viscosity, cSt		
@ 40oC	ASTM D445	460
@ 100oC	ASTM D445	30
Viscosity Index	ASTM D2270	95
Flash Point (COC), oC	ASTM D92	222
Pour Point, oC	ASTM D97	-9

Version 03/21



AP Oil Pte. Ltd.
A member of AP Oil Int'l Ltd

18 Pioneer Sector 1, Jurong, Singapore 628428
tel 65 6861 5503 fax 65 6861 9162

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.