

S.O GEAR OIL XP-HD

HIGH PERFORMANCE AUTOMOTIVE GEAR OIL

DESCRIPTION

S.O GEAR OIL XP-HD is premium extreme pressure automotive gear oil fortified with sulphur-phosphorus and ashless dispersant additives to enhance anti-wear under heavy loading, anti corrosion, anti oxidant, demulsification and anti-foam properties. This oil meets the performance requirements of API service GL-5, MT-1 and MIL-PRF-2105E, and is particularly recommended for hypoid gears, steering boxes and differential gears operating under critically severe conditions.

CHARACTERISTICS

- Outstanding protection against wear and shock
- Excellent thermal stability
- Excellent rust and corrosion inhibition
- Exceptional load-carrying capability
- Extends gear equipment life

APPLICATION

S.O GEAR OIL XP-HD is recommended for hypoid gears, steering boxes, and differential gears operating under critically severe conditions.

TYPICAL SPECIFICATION

SAE GRADE		90
Kinematic Viscosity, cSt		
@ 40oC	ASTM D445	197
@ 100oC	ASTM D445	18
Viscosity Index	ASTM D2270	96
Flash Point (COC), oC	ASTM D92	212
Pour Point, oC	ASTM D97	-10

Version 03/21